

Address: Jincheng Road, Xiaoshan, Hangzhou, Zhejiang, China PC CODE: 311201

Tel: +86-571-22860158 Fax: +86-571-22860159

Website: www.sypigment.com Email: sy@sypigment.com

# Material Safety Data Sheet

According to Directive 91/155/EEC

#### **PIGMENT YELLOW 74**

(PY74)

#### 1. SUBSTANCE/PREPARATION AND COMPANY

**Chemical characterization:** 

Company: SY CHEMCIAL CO., LTD.

Add.: Jincheng Road, Xiaoshan, Hangzhou, China

Emial: sy@sypigment.com

Tel:+86-571-22860158 Fax:+86-571-22860159

#### 2. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical nature:

 Chemical Formula:
 C<sub>18</sub>H<sub>18</sub>N<sub>4</sub>O<sub>6</sub>

 C.I.No.:
 11741

 C.A.S.No.:
 6358-31-2

#### 3. HARZARD INENTIFICATION

Critical hazards to man and the environment: None

#### 4. FIRST-AID MEASURES

General advice: Remove contaminated clothing.

If inhaled: Keep patient calm, remove to fresh air and treat symptomatically
On skin contact: Wash with soap and water, if symptoms occur, consult physician

On contact with eyes: Wash affected eyes for at least 15 minutes under running water with eyelids held open,

consult an eye specialist

On ingestion: Rinse month and then drink plenty of water

#### 5. FIRE-FIGHTING MEASURES

#### Suitable extinguishing media

Water spray, dry extinguishing media, foam

#### Extinguishing media which must not be used for safety reasons

High volume water jet

#### **Exposure hazards**

Contaminated water and soil must be disposed of conform to local regulations. Sufficient measures must be taken to retain water used for extinguishing.



Address: Jincheng Road, Xiaoshan, Hangzhou, Zhejiang, China PC CODE: 311201

Tel: +86-571-22860158 Fax: +86-571-22860159

Website: www.sypigment.com Email: sy@sypigment.com

# Material Safety Data Sheet

According to Directive 91/155/EEC

#### **PIGMENT YELLOW 74**

(PY74)

#### Special protective equipment for firefighters

Wear full and thick protective clothing. Wear self-contained breathing apparatus.

#### Hazardous decomposition products

Oxides of carbon, Toxic gases/vapours

#### 6. ACCIDENTAL RELEASE MEASURES

**Personal precautions:** Do not breathe dust

Environmental precautions: Do not let product enter drains. Avoid dust formation.

Method for cleaning up: Contain with dust binding material and dispose.

#### 7. HANDLING AND STORAGE

Handling: Breathing must be protected when large quantities are decanted without local exhaust

ventilation.

Protection against fir and explosion:

Take precautionary measures against static discharges.

Storage: Keep tightly closed in a dry, cool and well ventilated place, direct sources of heat must be

avoided and open containers must be allowed to stand over extend periods of time. Position

containers so that any labeling information on the container is visible.

Caution: Keep this product well sealed. Keep in cool, dry place. Close containers immediately after

use.

#### 8. EXPOSURE CONTROLS AND PERSONAL PROTECTION

Additional information on the lay-out of technical plant(See 7)

#### Personal protective equipment

**Technical measures/Precautions** 

No special precautions required

**Respiratory protection:** Do not breathe dust

**Eye protection:** Goggles **General safety and hygiene measures:** 

The usual precautions for the handling of chemicals must be observed

#### 9. PHYSICAL AND CHEMICAL PROPERTIES

Form: dry powder
Colour: YELLOW
Odour: Odourless
Change in physical state: N/A

Melting point/melting rang: High melting point



**Address**: Jincheng Road, Xiaoshan, Hangzhou, Zhejiang, China PC CODE: 311201 **Tel**: +86-571-22860158 **Fax**: +86-571-22860159

Website: www.sypigment.com Email: sy@sypigment.com

## Material Safety Data Sheet

According to Directive 91/155/E

#### **PIGMENT YELLOW 74**

(PY74)

Flash point: N/A, High melting material

**Explosion hazard:** N/A **Vapour pressure:** N/A

**Density,20°C:**  $1.43(g/cm^3)$ 

Approx.: N/A
Bulk density: N/A

**Average Particle size:** 0.5 to 2.50 Micron Meters

Solubility in water:

Solubility in other solvent:

N/A

PH Value:

6

#### 10. STABILITY ABD REACTION

Stability: Stable

Conditions to avoid: Against moisture

Incompatibility: Strong oxidizing agent

Hazardous decomposition products:

When involved in a fire, burning organic pigments may evolve moxious fumes which may include carbon monoxide, nitrous oxides, or other toxic compounds, depending on the

pigment type

Hazardous Polymerization: Will not occur
Conditions to avoid: None known

#### 11. TOXICOLOGICAL INFORMATION

Acute Toxicity: Acute oral LD50 value of 10000mg/kg or greater in rats

Sensitizing: No data available

#### 12. ECOLOGICAL INFORMATION

**Elimination information:** The products is not very soluble in water and can thus be virtually removed from water

mechanically in suitable effluent treatment plants.

#### 13. DISPOSAL CONSIDERATION

**Product:** Must be made in accordance with Federal State and local regulations.

Contaminated packaging: Uncontaminated packs can be re-used. Packs that cannot be cleaned should be disposed of

in the same manner as the contents.



Address: Jincheng Road, Xiaoshan, Hangzhou, Zhejiang, China PC CODE: 311201

Tel: +86-571-22860158

Fax: +86-571-22860159

Website: www.sypigment.com Email: sy@sypigment.com

# Material Safety Data Sheet

According to Directive 91/155/EEC

#### **PIGMENT YELLOW 74**

(PY74)

#### 14. TRANSPORT INFORMATION

Not classified as hazardous under transport regulations.

#### 15. REGULATORY INFORMATION

Labeling according to EEC directives

Not subject to labeling

National legislation/ regulations

Water hazard class: generally non water hazardous

#### 16. OTHER INFORMATION

N/A=not application

N.D.A.=no data available